



Spreaders & Seeder



High Quality Spreader/Seeders from Turf-Ex®

Corrosion-resistant polyethylene construction. Heavy-duty powder-coated steel frames and stainless steel spinners mean long life and excellent performance.

Available in Push Style, 12 Volt, PTO or Ground Drive options. Capacities from 1 to 12 cubic ft. to meet any spreader needs. The ideal choice for spreading grass seed, fertilizers, weed and pest control products and even pelletized lime.

Open/Close gates are controlled by a 10' push/pull cable on all units. Speed control is either 12 volt, PTO drive or ground drive. All models except push spreaders have a stainless steel adjustable fin spinner. Spreaders are designed to fit 2" receiver mount or Class 0/1 3-Point hitches as noted under each model. Weather covers are included with all spreaders.

Note: Model TS300 Series is designed for optional mounting kits to fit ATV's and riding mowers or trailer mounted for direct pull.

TS75 Push Spreader features 80 lbs. capacity. Manual open/close control at the handle. Tires are 13" pneumatic design. Spreading width up to 10'. Dimensions are 50" L x 28" H x 33" W.

TS300 Hitch Spreader features 3.0 cubic ft. capacity, (240 lbs.). (TS300) Manual open/close gate with 12-volt spinner control. (TS300EG) With electric gate and speed controller. Designed to fit 2" receivers. Spreading width up to 20'. Dimensions are 22" L x 30" H x 30" W. (Optional Mounting Kits: ATV's (DRM175), ZTR Mowers (ZTR175), Trailer Tow (TLR175).

TS700E Hitch Spreader features 7.0 cubic ft. capacity, (560 lbs.). Manual open/close gate with 12-volt spinner control. Fits Class 0/1 3-Point hitches. Spreading width up to 30'. Dimensions are 26" L x 29" H x 35" W.

TS700P PTO Drive Spreader features 7.0 cubic ft. capacity, (560 lbs.). Manual open/close gate. Spinner is controlled by implement PTO. Fits Class 0/1 3-Point hitches. Spreading width up to 30'. Dimensions are 26" L x 29" H x 35" W.

TS700GR Ground Drive Spreader features 7.0 cubic ft. capacity, (560 lbs.). Manual open/close gate. Spinner is controlled by ground drive speed. Integral trailer with 18" pneumatic tires is standard. Spreading width up to 30' at 5 mph. Dimensions are 26" L x 29" H x 35" W.

TS1200E Hitch Spreader features 12.0 cubic ft. capacity, (960 lbs.). Manual open/close gate with 12-volt spinner control. Fits Class 0/1 3-Point hitches. Spreading width up to 30'. Dimensions are 30" L x 30" H x 44" W.

TS1200P PTO Spreader features 12.0 cubic ft. capacity, (960 lbs.). Manual open/close gate. Spinner is controlled by implement PTO. Fits Class 0/1 3-Point hitches. Spreading width up to 30'. Dimensions are 30" L x 30" H x 44" W.

TS1200GR Ground Drive Spreader features 12.0 cubic ft. capacity, (960 lbs.). Manual open/close gate. Spinner is controlled by ground drive speed. Integral trailer with 18" pneumatic tires is standard. Spreading width up to 30' at 5 mph. Dimensions are 30" L x 30" H x 44" W.



TS300 with DRM175 Kit



TS700GR & TS1200GR



Model TS75



Model TS700E & TS1200E



TS300 with ZTR175 Kit



TS300 with TLR175 Kit



TS700P & TS1200P PTO Unit

Part No.	Drive	Capacity	Wt.	Net Ea.
TZ TS75	Push	80 lbs.	25 lbs.	\$ 315.00
TZ TS300	12-Volt	3.0 cu. ft.	65 lbs.	809.50
TZ TS300EG	12-Volt *	3.0 cu. ft.	65 lbs.	1259.00
TZ TS700E	12-Volt	7.0 cu. ft.	100 lbs.	1349.00
TZ TS700P	PTO	7.0 cu. ft.	112 lbs.	1349.00
TZ TS700GR	Ground Drive	7.0 cu. ft.	172 lbs.	2249.00
TZ TS1200E	12-Volt	12.0 cu. ft.	112 lbs.	1529.00
TZ TS1200P	PTO	12.0 cu. ft.	120 lbs.	1529.00
TZ TS1200GR	Ground Drive	12.0 cu. ft.	180 lbs.	2699.00
TZ TLR175	Trailer Mount Kit for TS300			325.00
TZ DRM175	Mount Kit for TS300 & ATVs & Utility Vehicles			309.00
TZ ZTR175	Mount Kit for TS300 to ZTR Mowers			179.00
TZ ADF020	Deflector Kit for TS700 & TS1200 Series			89.50

* Electric Gate and speed controller.