



FEATURES

- GP-exclusive design
- New, stronger housing design for extra durability
- Improved trigger design for easier pull at high pressure
- Extra venting for improved performance at high temperatures
- Larger, more comfortable hand grip space to more readily accommodate work gloves

SPECIFICATIONS

Part Number:	YG5000
Maximum Volume	8.0 GPM
Maximum Pressure	5000 PSI
Maximum Temperature	320°F
Port Sizes: Inlet	3/8" NPT-F
Outlet	1/4" NPT-F
Dimensions	7" x 5" x 1.25"
Weight	1.2 lbs.
Materials	Brass, SST, Plastic, Viton, Buna

PARTS LIST

YG5000: 30.2510.17

No	Part No.	Description	Kit	Qty
*	YKITG5000	REPAIR KIT, YG5000		
•	Y30260924	HOUSING KIT		
†	Y30170820	SEAT KIT		
1.	Y16307700	Screw, M3.5 x 18mm long	•	7
2.	Y30250684	Trigger		1
3.	Y30067584	Striker		1
4.	Y30251731	Pin, 5 x 27.5 mm		1
5.	Y30200835	Tube, 1/4"-NPT		1
6.	Y30259735	Body, Brass		1
7.	Y30260284	Plastic Housing, Left	•	1
8.	Y30151084	Safety Latch, Red		1
9.	Y30253435	Tube, 3/8"-NPT-F		1
10.	Y30258384	Plastic Housing, Right	•	1
11.	Y10401800	Back-up Ring, 7.5 x 3.2 x 1.2 mm	*	1
12.	Y10316500	O-Ring, 2.62 x 84 mm, Viton	*	1
13.	Y14351100	Brass Washer, 3.2 x 7 x 0.5 mm		1
14.	Y30251651	SS Piston, 4 x 44 mm	*	1
15.	Y30259651	SS Spring		1
16.	Y10302002	O-ring, 1.5 x 10 mm	*	1
17.	Y30259531	Spring Housing Plug		1
18.	Y14744800	5/16" SS Ball	*	1
19.	Y30051251	SS Seat, Ø 6 x 11 x 4.5	* †	1
20.	Y10305501	O-ring, 1.78 x 7.66 mm	* †	1

